Package: rym (via r-universe)

October 16, 2026

Type Package

Title R Interface to Yandex Metrica API

Version 1.1.0

Maintainer Alexey Seleznev <selesnow@gmail.com>

Description Allows work with 'Management API' for load counters, segments, filters, user permissions and goals list from Yandex Metrica, 'Reporting API' allows you to get information about the statistics of site visits and other data without using the web interface, 'Logs API' allows to receive non-aggregated data and 'Compatible with Google Analytics Core Reporting API v3' allows receive information about site traffic and other data using field names from Google Analytics Core API. For more information see official documents <https://yandex.ru/dev/metrika/doc/api2/concept/about-docpage>.

Depends R (>= 3.5.0)

BugReports https://github.com/selesnow/rym/issues

Suggests knitr, rmarkdown

VignetteBuilder knitr

License GPL-2

Imports httr, httr2, stringr, utils, purrr

URL https://selesnow.github.io/rym/

Encoding UTF-8

Language ru

Config/pak/sysreqs libicu-dev libssl-dev

Repository https://selesnow.r-universe.dev

Date/Publication 2026-05-19 14:50:41 UTC

RemoteUrl https://github.com/selesnow/rym

RemoteRef HEAD

RemoteSha 2abdcf2b270ccd12f51bde5fae02ae10f6507af8

Contents

rym-package . . . 2
rym-calls . . . 4
rym-expense-uploading . . . 6
rym-offline-conversion . . . 8
rym_add_goal . . . 11
rym_add_segment . . . 12
rym_auth . . . 13
rym_get_counters . . . 14
rym_get_data . . . 15
rym_get_direct_clients . . . 16
rym_get_filters . . . 17
rym_get_ga . . . 18
rym_get_goals . . . 20
rym_get_logs . . . 21
rym_get_my_logins . . . 22
rym_get_segments . . . 23
rym_users_grants . . . 24

Index **25**

`rym-package` *R Interface to Yandex Metrica API*

Description

Allows work with 'Management API' for load counters, segments, filters, user permissions and goals list from Yandex Metrica, 'Reporting API' allows you to get information about the statistics of site visits and other data without using the web interface, 'Logs API' allows to receive non-aggregated data and 'Compatible with Google Analytics Core Reporting API v3' allows receive information about site traffic and other data using field names from Google Analytics Core API. For more information see official documents <https://yandex.ru/dev/metrika/doc/api2/concept/about-docpage>.

Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.

Author(s)

Alexey Seleznev [aut, cre] (ORCID: <https://orcid.org/0000-0003-0410-7385>), Netpeak [cph]

Maintainer: Alexey Seleznev <selesnow@gmail.com>

References

Officialrym documents

Management API Documents

Reporting API Documents

API Compatible with Google Analytics Core API v3

Logs API Documentations

Or read vignettes:

```
vignette("intro-to-rym", package = "rym")
vignette("rym-management-api", package = "rym")
vignette("rym-reporting-api", package = "rym")
vignette("rym-ga-api", package = "rym")
vignette("rym-logs-api", package = "rym")
```

Examples

```
## Not run:
library(rym)

# get counters list
my_counters <- rym_get_counter()

# join all counters id in string format, like 1,2,3,4,5,...,n
counters_ids <- paste0(my_counters$id, collapse = ",")

# get statistic from reporting API
reporting <- rym_get_data(counters   = counters_ids,
                          date.from  = "2018-08-01",
                          date.to    = "yesterday",
                          dimensions = "ym:s:date,
                            ym:s:lastTrafficSource",
                          metrics    = "ym:s:visits,
                      ym:s:pageviews,
                      ym:s:users",
                          sort       = "-ym:s:date")

# get raw data
raw_data <- rym_get_logs(counter = counters_ids[1],
                               date.from = "2016-12-01",
                               date.to = "2016-12-20",
                               fields = "ym:s:visitID,
                    ym:s:date,
          ym:s:bounce,
          ym:s:clientID,
          ym:s:networkType",
                               source = "visits")

## End(Not run)
```

rym-calls *Manage callss*

Description

calls Management:

rym_enable_calls Enable calls tracking for the specified counter.

rym_disable_calls Disable calls tracking for the specified counter.

rym_upload_calls Upload callss.

rym_allow_calls Returns the date and time from which conversions can be linked to visits for the specified counter.

rym_get_uploadings_callss Returns a list of calls downloads.

Usage

```
rym_enable_calls(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_disable_calls(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_allow_calls(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_upload_calls(
   counter,
   data,
   client.id.type = c("CLIENT_ID", "USER_ID"),
   new.goal.name  = NULL,
   comment        = paste0("Upload by rym at ", Sys.time()),
   login          = getOption("rym.user"),
   token.path     = getOption("rym.token_path"))

rym_get_uploadings_calls(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))
```

Arguments

`counter`	Your yandex metrica counter
`data`	data.frame, expense data for loading
`client.id.type`	Type of visitor identifiers: CLIENT_ID or USER_ID
`comment`	Comment for data loading
`new.goal.name`	The name of the new goal for calls in the event that such a goal does not exist. If the target exists, this parameter is ignored
`login`	character, Your Yandex login
`token.path`	character, Directory for store API credential

Details

Loading data format.

Require:

UserId, ClientId, Yclid Identifier of the visitor to the site or advertising campaign in Yandex.Direct, for example: 12345

Optional:

StaticCall whether the call is static (1 - static, 0 - dynamic)

Price target price, the decimal separator is the dot (.)

Currency currency in the three-letter format ISO 4217, for example: RUB

PhoneNumber phone number without spaces (with country and city code). For example, +70123456789

TalkDuration call duration in seconds

HoldDuration call waiting time in seconds

CallMissed whether the call is missed (1 - missed, 0 - answered)

Tag custom label. It can be used to mark the quality of a call or its outcome, etc. For example, "the customer was not satisfied with the price"

FirstTimeCaller primary (1 - primary call, 0 - secondary call)

URL The URL from which the call came (the page associated with the event). For example, this could be the landing page for an ad campaign that has a phone number (PhoneNumber)

CallTrackerURL The URL to go to the call tracker interface

Example of CSV file.

Author(s)

Alexey Seleznev

References

See official dox: API documents Upload calls info into Yandex Metrica Calls in Yandex Metrica

Examples

```
## Not run:
# read data for upload
data <- read.csv("https://bit.ly/2CcsNyl")

# enable offline cnversion
rym_enable_calls(
   counter = 123456789,
   login   = "your_login"
)

# upload data
rym_upload_calls(
   counter        = 123456789,
   data           = data,
   client.id.type = "CLIENT_ID",
   login          = "your_login")

# check uploading
rym_allow_calls(
   counter = 123456789,
   login   = "your_login")

## End(Not run)
```

`rym-expense-uploading` *Manage Cost Data Upload*

Description

Upload, delete and get list of uploading expense data in 'Yandex Metrica'.

Usage

```
rym_upload_expense(
    counter,
    data,
    comment    = paste0("Upload bt rym at ", Sys.time()),
    login      = getOption("rym.user"),
    token.path = getOption("rym.token_path"))

rym_delete_uploaded_expense(
    counter,
    data,
    comment    = paste0("Upload bt rym at ", Sys.time()),
    login      = getOption("rym.user"),
    token.path = getOption("rym.token_path"))
```

```
rym_get_uploadings_expense(
    counter,
    login      = getOption("rym.user"),
    token.path = getOption("rym.token_path"))
```

Arguments

counter	Your yandex metrica counter
data	data.frame, expense data for loading
comment	Comment for data loading
login	character, Your Yandex login
token.path	character, Directory for store API credential

Details

Loading data format.

Require:

Date Date in YYYY-MM-DD format

UTMSource Source name, for example google

Expenses Expense size, for example 12.34

Optional:

UTMMedium Medium name, for exmaple cpc

UTMCampaign Campaign name, for example my campaing

UTMTerm Term name, for example my term

UTMContent Content name, for example my contant

Currency Currency in ISO 4217 code

Clicks Clicks number, for example 23

Author(s)

Alexey Seleznev

References

See official dox: API documents Yandex Metrica documents

Examples

```
## Not run:
# prepare data for loading
expense <- data.frame(Date        = c("2020-06-01",
                                      "2020-06-02"),
                      UTMSource   = c("test_s_1",
                                      "test_s_2"),
                      Expenses    = c(88.12,
                                      92.11),
                      UTMMedium   = c("cpc",
                                      "cpm"),
                      UTMCampaign = c("camp1",
                                      "camp2"),
                      UTMTerm     = c("term1",
                                      "term2"),
                      UTMContent  = c("cont1",
                                      "cont2"),
                      Currency    = c("RUB",
                                      "RUB"),
                      Clicks      = c(11, 15))

# upload data
rym_upload_expense(
                counter = 1111111,
                data    = expense,
                login   = 'yandex_login')

# delete data
rym_delete_uploaded_expense(
                counter = 1111111,
                data    = expense,
                login   = 'yandex_login')

# get list of expense uploadings
loaded <- rym_get_uploadings_expense(
                counter = 1111111,
                login   = 'yandex_login')


## End(Not run)
```

`rym-offline-conversion` *Manage offline conversions*

Description

Offline Conversion Management:

rym_enable_offline_conversion Enable offline conversion tracking for the specified counter.

rym_disable_offline_conversion Disable offline conversion tracking for the specified counter.

rym_upload_offline_conversion Upload offline conversions.

rym_allow_offline_conversion Returns the date and time from which conversions can be linked to visits for the specified counter.

rym_get_uploadings_offline_conversions Returns a list of offline conversion downloads.

Usage

```
rym_enable_offline_conversion(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_disable_offline_conversion(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_allow_offline_conversion(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))

rym_upload_offline_conversion(
   counter,
   data,
   client.id.type = c("CLIENT_ID", "USER_ID"),
   comment        = paste0("Upload by rym at ", Sys.time()),
   login          = getOption("rym.user"),
   token.path     = getOption("rym.token_path"))

rym_get_uploadings_offline_conversions(
   counter,
   login      = getOption("rym.user"),
   token.path = getOption("rym.token_path"))
```

Arguments

counter	Your yandex metrica counter
data	data.frame, expense data for loading
client.id.type	Type of visitor identifiers: CLIENT_ID or USER_ID
comment	Comment for data loading
login	character, Your Yandex login
token.path	character, Directory for store API credential

Details

Loading data format.

Require:

UserId, ClientId, Yclid Identifier of the visitor to the site or advertising campaign in Yandex.Direct, for example: 12345

Target Target ID specified when creating the target, for example order_confirmed

DateTime The time at which the conversion occurred in Unix Time Stamp format. Indicate the time in the time zone UTC + 0, for example: 1481718166

Optional:

Price Goal Value, for example: 1000

Currency Three-letter currency code according to ISO 4217, for example: RUB

Example of CSV file.

Author(s)

Alexey Seleznev

References

See official dox: API documents Yandex Metrica documents

Examples

```
## Not run:
# read data for upload
data <- read.csv("https://bit.ly/2CcsNyl")

# enable offline cnversion
rym_enable_offline_conversion(
   counter = 123456789,
   login   = "your_login"
)

# upload data
rym_upload_offline_conversion(
   counter        = 123456789,
   data           = data,
   client.id.type = "CLIENT_ID",
   login          = "your_login")

# check uploading
rym_allow_offline_conversion(
   counter = 123456789,
   login   = "your_login")

## End(Not run)
```

rym_add_goal *Create goal in 'Yandex Metrica'*

Description

Create new goal in 'Yandex Metrica' counter.

Usage

```
rym_add_goal(
    counter,
    name,
    type = c("number","action","step","url"),
    is.retargeting = FALSE,
    flag = c(NA, "basket", "order"),
    conditions = NULL,
    login = getOption("rym.user"),
    token.path = getOption("rym.token_path"))
```

Arguments

counter	Yandex Metrika counter ID
name	character, goal name
type	character, goal type, one of "number","action","step","url"
is.retargeting	boolean, if TRUE the goal is retargeting
flag	character, target type for Yandex.Market customers
conditions	list, the list of conditions, for example `list(type = 'exact', url = 'rym-first-goal')`
login	character, Your Yandex login
token.path	character, Directory for store API credential

Author(s)

Alexey Seleznev

References

Official docs of 'Yandex Metrica Management API'

Examples

```
## Not run:
rym_add_goal(123456789,
             name = 'first_goal',
             type = 'action',
             conditions = list(type = 'exact',
                               url = 'rym-first-goal'),
```

```
              login = 'your_login')

## End(Not run)
```

`rym_add_segment` *Create segment in 'Yandex Metrica'*

Description

Create a new API segment in 'Yandex Metrica' counter.

Usage

```
rym_add_segment(
     counter,
     name,
     expression,
     login = getOption("rym.user"),
     token.path = getOption("rym.token_path"))
```

Arguments

`counter`	Yandex Metrika counter ID
`name`	character, segment name
`expression`	character, filter expression, for example `"ym:s:trafficSource=='organic' AND ym:s:isNewUser=='Yes'"`, for more information go link
`login`	character, Your Yandex login
`token.path`	character, Directory for store API credential

Author(s)

Alexey Seleznev

References

Official docs of 'Yandex Metrica Management API'

See Also

See `rym_add_goal()` for create new goal in 'Yandex Metrica'.

Examples

```
## Not run:
rym_add_segment(
     counter = 123456789,
     name = "my_segment",
     expression = "ym:s:trafficSource=='organic' AND ym:s:isNewUser=='Yes'",
     login = "your_login")


## End(Not run)
```

---

rym_auth *Authentication in Yandex Metrika API*

Description

Actually you don't need call rym_auth since it will be called when you run any of the functions available in rym.

Usage

```
rym_auth(login = getOption("rym.user"),
         new.user = FALSE,
         token.path = getOption("rym.token_path"))
```

Arguments

login	character, Your Yandex login
new.user	logical, If TRUE you reauth in Yandex Metrika API
token.path	character, Directory for store API credential

Details

All your credential save in directory specified in the argument token.path, after save every time you run any function from rym, rym_auth be load credentials from local file login.rymAuth.RData. rym_auth create files for each your logins, which makes it possible use many yandex account in one script. Every tokens expire after 1 year after authentication, but rym_auth automaticly refresh and save you credential 30 days before he expire.

Value

List with credential data.

Author(s)

Alexey Seleznev

References

OAuth 2.0 in Yandex docs - https://tech.yandex.ru/oauth/doc/dg/concepts/about-docpage/

Examples

```
## Not run:
library(rym)
rym_auth(login = "my_login")

## End(Not run)
```

`rym_get_counters` *Load Yandex Metrica counters*

Description

Returns a list of existing counters available to the user.

Usage

```
rym_get_counters(login = getOption("rym.user"),
                 token.path = getOption("rym.token_path"),
                 search.string = NULL)
```

Arguments

`login`	character, Your Yandex login
`token.path`	character, Directory for store API credential
`search.string`	character, Filter by line. Counters will be displayed, the identifier, name, site or mirrors of which contain the specified substring

Value

Data frame with list of yandex metrica counters.

Author(s)

Alexey Seleznev

References

Official docs - https://tech.yandex.ru/metrika/doc/api2/management/counters/counters-docpage/

Examples

```
## Not run:
my_counters <- rym_get_counters(login = "my_login")

## End(Not run)
```

rym_get_data *Load data by compatible with the 'Google Analytics Core Reporting API'*

Description

The Reporting API allows you to obtain information about site visits statistics and other data without using the Yandex.Metrica interface.

Usage

```
rym_get_data(direct.client.logins = NULL, counters,
  metrics = "ym:s:visits,ym:s:pageviews,ym:s:users",
  dimensions = NULL, filters = NULL,
  sort = NULL, date.from = "8daysAgo",
  date.to = "yesterday", accuracy = "full",
  include.undefined = TRUE, lang = "ru",
  timezone = NULL, pretty = FALSE,
  login = getOption("rym.user"),
  token.path = getOption("rym.token_path"))
```

Arguments

direct.client.logins	Logins of Yandex.Direct clients, separated by commas. Can be used to generate a Direct Expense report.
counters	Counter identifiers, separated by commas.
metrics	A list of metrics, separated by a comma.
dimensions	A list of groupings, separated by a comma.
filters	A list of filtring data.
sort	A list of metrics and dimension for sorting result data, for desc sorting use -.
date.from	Start date in YYYY-MM-DD.
date.to	End date in YYYY-MM-DD.
accuracy	Sampling level, one of low, medium, high or full. Or numeric from 0 to 1, where 1 - no sampling.
include.undefined	Includes in response rows for which grouping values are not defined.
lang	Language, by default ru
timezone	Timezone for time data.
pretty	Specifies the formatting of the result.
login	character, Your Yandex login
token.path	character, Directory for store API credential

Details

This API have some limits. 1. 10 demensions in the query. 2. 20 metrics in one query. 3. Limit: the number of unique groupings and metrics is up to 10, the number of individual filters is up to 20, the length of the line in the filter is up to 10,000 characters.

Value

Data frame with dimension and metrics.

Author(s)

Alexey Seleznev

References

Reporting API docs

Run `vignette("rym-reporting-api", package = "rym")` to see the corresponding vignette.

See Also

For load statics you also can use `rym_get_ga` and `rym_get_logs`

Examples

```
## Not run:
test_data <- rym_get_data(counters = 26841129,
                          dimensions = "ym:s:date,
                                        ym:s:lastsignTrafficSource",
        login = "my_login",
        sort = "ym:s:date")

## End(Not run)
```

---

rym_get_direct_clients

Load Yandex.Direct clients

Description

Returns data about Yandex.Direct clients for campaigns that the owner of the Metrics counter has access to.

Usage

```
rym_get_direct_clients(counters, login = getOption("rym.user"),
                       token.path = getOption("rym.token_path"))
```

Arguments

counters	Counter identifiers, separated by commas
login	character, Your Yandex login
token.path	character, Directory for store API credential

Value

Data frame with Yandex Direct clients.

Author(s)

Alexey Seleznev

References

Reporting API docs

Examples

```
## Not run:
my_clients <- rym_get_direct_clients(counters="11111,22222",
                                     login = "my_login")

## End(Not run)
```

---

rym_get_filters *List of filters*

Description

Returns information about counter filters.

Usage

```
rym_get_filters(counter, login = getOption("rym.user"),
                token.path = getOption("rym.token_path"))
```

Arguments

counter	Yandex Metrika counter ID, you can get ids of all your conters over rym_counters
login	character, Your Yandex login
token.path	character, Directory for store API credential, by default is your work directory

Value

Data frame with list of yandex metrika counter filters

id	Filter id.
attr	The type of data to which the filter applies. One of referer, uniq_id, client_ip, title, url.
type	The relation or action for the filter, equal, contain, me, start, interval, only_mirrors.
value	Filter value.
action	Type of filter, include or exclude.
status	Status of filter, active or disabled.
with_subdomains	Filter by subdomains.
start_ip	The first IP address of the range.
start_ip	The last IP address of the range.

Author(s)

Alexey Seleznev

References

Official docs

Examples

```
## Not run:
filters <- rym_get_filters(counter    = "your_counter_id",
                           login      = "your_login")

## End(Not run)
```

`rym_get_ga` *Work with 'compatible with the Google Analytics Core Reporting API (v3)'*

Description

Allows you to perform the following operations: 1. Obtain information about site traffic and other data. 2. Integrate Yandex.Metrica data with applications developed with the 'Google Analytics Core Reporting API (v3)' in mind. 3. Use the usual query parameters when collecting statistics, if you previously worked with the Google Analytics Core Reporting API (v3).

Usage

```
rym_get_ga(start.date = "10daysAgo", end.date = "today",
  counter = NULL, dimensions = "ga:date,ga:sourceMedium",
  metrics = "ga:sessions,ga:bounces,ga:users",
  filters = NULL, sort = NULL,
  sampling.level = "HIGHER_PRECISION",
  login = getOption("rym.user"),
  token.path = getOption("rym.token_path"))
```

Arguments

start.date	Start date in format YYYY-MM-DD
end.date	End date in format YYYY-MM-DD
counter	Your yandex metrica counter
dimensions	List of dimensions fields, for example "ga:browser,ga:city", see dictionary of available dimension
metrics	List of metrics fields, for example "ga:users,ga:sessions", see dictionary of available metrics
filters	List of filtrind dimensions and metrics.
sort	Sorting fields
sampling.level	One of "HIGHER_PRECISION", "FASTER", "DEFAULT"
login	character, Your Yandex login
token.path	character, Directory for store API credential

Details

Limits: 10 metrics for one query. 7 dimensions for one query

Value

Data frame with fields.

Author(s)

Alexey Seleznev

References

Official compatible with the Google Analytics Core Reporting API (v3) docs

Run `vignette("rym-ga-api", package = "rym")` to see the corresponding vignette.

See Also

For load statics you also can use `rym_get_data()` and `rym_get_logs()`

Examples

```
## Not run:
data <- rym_get_ga(start.date = "2017-08-01",
                   end.date = "yesterday",
                   counter = "ga:26841129",
                   metrics = "ga:sessions,ga:bounces,ga:users",
                   dimensions = "ga:date,ga:sourceMedium",
                   login      = "my_login")

## End(Not run)
```

`rym_get_goals` *List of goals*

Description

Returns information about the purpose of the yandex metrica counter.

Usage

```
rym_get_goals(counter, login = getOption("rym.user"),
          token.path = getOption("rym.token_path"))
```

Arguments

`counter`	Yandex Metrika counter ID
`login`	character, Your Yandex login
`token.path`	character, Directory for store API credential

Value

Data frame with list of yandex metrica counters

Author(s)

Alexey Seleznev

References

Official docs of 'Yandex Metrica Management API'

Docs on rym website

Run `vignette("rym-management-api", package = "rym")` to see the corresponding vignette.

Examples

```
## Not run:
my_counters <- rym_get_goals(login = "my_login")

## End(Not run)
```

rym_get_logs *Get raw data from yandex metrika.*

Description

'Logs API' allows you to receive non-aggregated data collected by Yandex.Metrica. This API is intended for service users who want to independently process statistical data and use them to solve unique analytical problems.

Usage

```
rym_get_logs(counter = NULL, date.from = Sys.Date() - 10, date.to =
    Sys.Date() - 1, fields =
    "ym:s:date,ym:s:counterID,ym:s:dateTime,
 ym:s:isNewUser,ym:s:startURL,ym:s:visitDuration,
 ym:s:ipAddress,ym:s:referer",
    source = "visits", login = getOption("rym.user"),
 token.path = getOption("rym.token_path"))
```

Arguments

counter	Yandex metrika counter id
date.from	Start date in format YYYY-MM-DD
date.to	End date in format YYYY-MM-DD
fields	List of fields
source	Log source, one of "hits" or "visits"
login	character, Your Yandex login
token.path	character, Directory for store API credential

Value

Data frame with values and fields

Author(s)

Alexey Seleznev

References

Visits fields

Hits fields

Logs API docs

Docs on rym website

Run `vignette("rym-logs-api", package = "rym")` to see the corresponding vignette.

See Also

For load statics you also can use `rym_get_data()` and `rym_get_ga()`

Examples

```
## Not run:
# where "00000000" is your counter id
rawmetrikdata <- rym_get_logs(counter = "00000000",
                              date.from = "2016-12-01",
                              date.to = "2016-12-20",
                              fields = "ym:s:visitID,
                    ym:s:date,
          ym:s:bounce,
          ym:s:clientID,
          ym:s:networkType",
                              source = "visits")

## End(Not run)
```

`rym_get_my_logins` *Show list of auth logins*

Description

Get login list, chose and set default yandex login in current R session.

Usage

```
rym_get_my_logins(token.path = getOption("rym.token_path"),
                  set.login = TRUE)
```

Arguments

`token.path`	character, Directory for store API credential
`set.login`	logical, if TRUE you set one of your account as session default

Author(s)

Alexey Seleznev

Examples

```
## Not run:
rym_get_my_logins()

## End(Not run)
```

`rym_get_segments` *List of segments*

Description

Returns a list of segments created using the API and related to the specified counter.

Usage

```
rym_get_segments(counter, login = getOption("rym.user"),
                 token.path = getOption("rym.token_path"))
```

Arguments

`counter`	Yandex Metrika counter ID, you can get ids of all your conters over rym_counters
`login`	character, Your Yandex login
`token.path`	character, Directory for store API credential, by default is your work directory

Value

Data frame with list of yandex metrica counter segments

`id`	Segment id.
`counter_id`	Yandex Metrica counter id.
`name`	Segment name.
`expression`	An expression that matches the value of the filters parameter.
`is_retargeting`	Logical, is retargeting segment or not.
`segment_source`	Source of the segment. Indicates how to create it. Accepts the value of api - segments that are created using the API are used.

Author(s)

Alexey Seleznev

References

Official docs of Yandex Metrica Management API

Docs on rym website

Run `vignette("rym-management-api", package = "rym")` to see the corresponding vignette.

Examples

```
## Not run:
segments <- rym_get_segments(counter    = "your_counter_id",
                             login      = "your_login")

## End(Not run)
```

rym_users_grants *List of users permissions*

Description

Returns information about the permissions to manage the counter and viewing statistics from 'management API'.

Usage

```
rym_users_grants(counter, login = getOption("rym.user"),
                 token.path = getOption("rym.token_path"))
```

Arguments

counter	Yandex Metrika counter ID, you can get ids of all your conters over rym_counters
login	character, Your Yandex login
token.path	character, Directory for store API credential, by default is your work directory

Value

Data frame with list of yandex metrika counter users

user_login	Login of the user who has been given permission to manage the counter.
perm	Access level, one of view, edit, public_stat.
created_at	Date of granting access in the format YYYY-MM-DD'T'hh: mm: ssZ.
comment	An arbitrary comment. The number of characters can not exceed 255.
partner_data_access	Logical, is partner access or not.

Author(s)

Alexey Seleznev

References

Official docs

Run `vignette("rym-management-api", package = "rym")` to see the corresponding vignette.

Examples

```
## Not run:
users <- rym_users_grants(counter    = "your_counter_id",
                          login      = "your_login")

## End(Not run)
```

Index

rym *(rym-package)*, 2
rym-calls, 4
rym-expense-uploading, 6
rym-offline-conversion, 8
rym-package, 2
rym_add_goal, 11
rym_add_goal(), *12*
rym_add_segment, 12
rym_allow_calls *(rym-calls)*, 4
rym_allow_offline_conversion
(rym-offline-conversion), 8
rym_auth, 13
rym_delete_uploaded_expense
(rym-expense-uploading), 6
rym_disable_calls *(rym-calls)*, 4
rym_disable_offline_conversion
(rym-offline-conversion), 8
rym_enable_calls *(rym-calls)*, 4
rym_enable_offline_conversion
(rym-offline-conversion), 8
rym_get_counters, 14
rym_get_data, 15
rym_get_data(), *19*, *22*
rym_get_direct_clients, 16
rym_get_filters, 17
rym_get_ga, *16*, 18
rym_get_ga(), *22*
rym_get_goals, 20
rym_get_logs, *16*, 21
rym_get_logs(), *19*
rym_get_my_logins, 22
rym_get_segments, 23
rym_get_uploadings_calls *(rym-calls)*, 4
rym_get_uploadings_expense
(rym-expense-uploading), 6
rym_get_uploadings_offline_conversions
(rym-offline-conversion), 8
rym_upload_calls *(rym-calls)*, 4
rym_upload_expense
(rym-expense-uploading), 6
rym_upload_offline_conversion
(rym-offline-conversion), 8
rym_users_grants, 24